

## Requirements For Secondary Suites

"Secondary Suite" means a *dwelling unit* which is accessory to the principle use being made of the lot upon which the secondary suite is located:

(a) having a floor space less than 40% of the habitable floor space of the building;


A site plan showing the access to the Secondary Suite

- (b) located within a building of residential occupancy containing only one other dwelling unit; and
- (c) located within and a part of a building that is classified as a single real estate entity.


## SECONDARY SUITE APPLICATION SUBMISSIONS FOR BUILDING PERMIT

☐ Building Permit Application (please see the digital Building Permit Application Procedure Handout), as well as Owner's Authorization Form, and Damage to Infrastructure form.
☐ Copy of Certificate of Title (Title certificates are only valid thirty (30) days from when they are downloaded from Land Titles; City Staff are able to "pull" title for your application, a charge will be applied when your application is submitted to the Building Division).
☐ Plans showing all the required information:
Floor plans drawn to scale showing
<ul> <li>The overall floor plans for the existing building with dimensions</li> </ul>
<ul> <li>Fire separation location, rating and construction details</li> </ul>
<ul> <li>Fire resistance rating and details of load bearing elements (walls, beams, columns</li> </ul>
<ul> <li>Proposed sound rating assemblies and details</li> </ul>
<ul> <li>Heating and ventilation details</li> </ul>
<ul> <li>Suite layout showing room users, door sizes and swing, bedrooms, etc. with dimensions</li> </ul>
<ul> <li>Bedroom window sizes, including location and dimensions of window wells</li> </ul>
<ul> <li>Smoke alarm locations and type</li> </ul>
<ul> <li>Mechanical room location and separation.</li> </ul>
<ul> <li>Calculation of floor area (suite must not exceed 40% of the habitable floor space of the building)</li> </ul>

## Suite Plan - Example



## Fire Separation Example



-(Note 1) Rated gypsum board is required on both sides of walls and underside of joists separating the house from the secondary suite.

-(Note 2) Openings for bathroom fans, pot lights larger than 5" or any other opening greater than 25 square inches in a fire separation shall be lined with rated gypsum board to maintain the fire separation. Joints in the gypsum board shall be taped and filled and fasteners shall be filled.

-(Note 3) Combustible plumbing pipes shall be covered by gypsum board.